





Head Office 12 Park Terrace, Bowden South Australia 5007

PO Box 103 Hindmarsh South Australia 5007 Telephone (08) 8440 0500 International +61 8 8440 0500

Facsimile (08) 8346 0845 International +61 8 8346 0845

Internet www.clipsal.com/cis E-Mail cis@clipsal.com.au

CIS Technical Support Hotline 1300 722 247

NSW	Sydney Albury	(02) 9794 920 (02) 6041 237
VIC	Melbourne Country Areas	(03) 9207 320 1800 653 89
QLD	Brisbane Townsville	(07) 3244 744 (07) 4729 333
SA	Adelaide	(08) 8268 040
WA	Perth	(08) 9442 444
TAS	Launceston	(03) 6343 590

### International Enquiries

International Sales and Marketing
Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au

New Zealand
Clipsal Industries (NZ) Ltd
Telephone +64 9 576 3403
Facsimile +64 9 576 1015
E-Mail headoffice@clipsal.co.nz

Customer Service
Free Facsimile (0508) 250 305
Auckland/Mobile Phone (09) 572 0014
Free Phone (0508) CLIPSAL
2547725

Malaysia
Clipsal Integrated Systems (M) Sdn Bhd
Level 3, Unit 3-2, C P Tower
No.11, Jalan 16/11, Seksyen 16,
46350 Petaling Jaya, Selangor, Malaysia
Telephone +60 3 7665 3555
Facsimile +60 3 7665 3155
E-Mail sales@cisasia.com.my

Singapore
Clipsal Integrated Systems Pte Ltd
5, Fourth Chin Bee Road
619 699 Singapore Telephone +65 6266 1998
Facsimile +65 6266 3922
E-Mail sales@cisasia.com

Greece Schneider Electric AE Telephone +30 69 4646 3200

Hong Kong
Clipsal Integrated Systems (HK) Limited
Telephone +852 2487 0261

PT Clipsal Graha Nusantara Telephone +62 21 630 6430

Clipsal Korea Co. Ltd Telephone +82 31 708 9240

South Africa
Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

United Kingdom

India
Schneider Electric India Pvt Ltd
Telephone +91 11 5159 0000

Philippines

# United Arab Emirates


You can find this brochure and many others online in PDF format at: clipsal.com Follow the links off the home page or access the following page directly clipsal.com/wat\_lib\_pdf.cfm

## clipsal.com/cis

Clipsal Integrated Systems Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions specifications and other information in this catalogue are correct, no warranty is given in respect thereof an the company shall not be liable for any error therein.

All rights reserved.

This material is copyright under Australian and international laws. Except as permitted under the relevant law, no part of this work may be reproduce by any process without prior written permission of a by any process without prior written permission of and acknowledgement to Clipsal Integrated Systems Pty Ltd





Pure Glass.








## Product Specifications.

Catalogue Number: 5080NL Seri	es
C-Bus Supply Voltage	15-36V DC @ 22 mA required for normal operation. Does not provide current to the C-Bus Network.
AC Input Impedance	50kΩ @ 1kHz
Electrical Isolation	3.75 kV RMS from C-Bus to mains (provided externally to 5080 Series Unit)
Max. No. of Units on Network	50 Units
Control Functions	Load switching, dimming, timers, scene control
Status Indicators	User configurable Orange and Blue
Warm-Up Time	5 seconds
C-Bus Connection	One terminal block to accommodate 0.2-15 mm <sup>2</sup> (24-16 AWG)
Dimensions (L x W x H)	116 x 75 x 27mm
Base Depth (into wall)	15 mm
Mounting Centres	84 mm
Weight	132g
Operating Temperature Range	0 - 45°C
Operating Humidity Range	10 - 95% R.H.



Description  2 Gang Key Input Unit, Rectangular Style, Glass Fascia
Rectangular Style, Glass Fascia
1 C K   t       't
4 Gang Key Input Unit, Rectangular Style, Glass Fascia
6 Gang Key Input Unit, Rectangular Style, Glass Fascia
2 Gang Key Input Unit, Square Style, Glass Fascia
4 Gang Key Input Unit, Square Style, Glass Fascia
6 Gang Key Input Unit, Square Style, Glass Fascia



