p25 Flexible 6MP Indoor Camera

Modular • Ceiling Mounting • Competitive

MOBOTIX

Product: p25

180° panorama image

103° night image (< 0.5 lux)

Hemispheric Included

The new indoor camera products are especially designed to be very competitive and at the same time supporting all MOBOTIX features and functionalities. Due to short distances in indoor environments, the new indoor camera line is perfect for the MOBOTIX hemispheric technology to achieve 360° or 180° panorama views without any blind spots.

p25 – PT Ceiling

The p25 is a ceiling camera with a manual pan/tilt functionality, using the same diameter and clamps like the c25 for easier installations. Equipped with a telephoto lens, the p25 can be directed to a specific spot in the room. With a 103-degree lens and mounted in the corner of a room the p25 covers the entire room in 6MP resolution. A hemispheric version is available also. There will be a surface mount kit to cope with concrete ceilings.

MxAnalytics inside the Camera

Optional MxAnalytics supports people counting and heat map reporting inside the camera, with no PC necessary. This functionality is part of the camera and therefore avoids any bandwidth traffic. It is perfect for indoor locations like retail stores, museums, shops, health care centers, universities and schools.

Optional Accessories

With the optional MxBus-IO-Module the camera can manage two input lines, two 12 V outputs and the connection to other MxBus devices via a MxBus interface. The input lines are isolated and do not require any power supply to monitor a chain of door or window contacts over several hundred meters. The outputs can directly drive a relay to switch high power AC loads like lamps or motors. The MxBus is a two-wire encrypted IO-Bus developed by MOBOTIX and allows an easy and secure interface to several different IO-Boxes over 100 meters. The p25 supports two-way audio with an optional audio package incl. microphone and speaker.

Solution example*: €1,363

	i25	€428
	c25	€428
	p25	€448
	POE switch	€59

- **Standalone**
  Full functionality without compromises
- **Video Sensor**
  MxActivitySensor reducing false alarms
- **Event Recording**
  Onboard (SD card) & direct to NAS
- **MxAnalytics Optional**
  Heat map & people counting
- **Alarm Notification**
  E-mail, FTP & VoIP (SIP)
- **Communication**
  Two-way audio option
- **Power**
  Standard PoE below 4W

Ceiling

On-wall kit

Audio package

MxBus-IO-Module